

Air Scrubber

MINI EM BY AERUS

WITH CERTIFIED SPACE TECHNOLOGY™

INNOVATIVE AIR TREATMENT SYSTEM



2017 Space Technology
Hall of Fame Inductee



description

- Natural air system assembled onto the mini-split/HVAC system
- Discreet or concealed installation
- Low maintenance – no cleaning required
- Requires only 20 watts of electricity
- Made in the U.S.A.

applications

- Mounts externally onto existing mini-split/HVAC system
- Residential homes
- Apartments
- Small offices
- Efficiency apartments
- Nursing homes
- Protects mini-split heating and cooling systems from dust buildup

the technology

The Air Scrubber Mini EM by Aerus is an innovative, ozone-free, air treatment system that easily mounts externally onto existing Mini Split HVAC systems. When the Air Scrubber Mini EM by Aerus is properly installed and activated, advanced oxidizers are released into the air that immediately begin reducing

airborne pollutants. Our proprietary ActivePure® Technology uses light waves and a catalytic process to produce scrubber ions that remove dust particles from the air. Our Certified Space Technology continuously protects and purifies the air, and attacks contaminants on all surfaces.*

*Published scientific studies conducted on behalf of activTek by Dr. James Marsden at Kansas State University demonstrated that activTek's ActivePure® Technology substantially reduces microbial populations on surfaces. The study's results are being provided solely for informational purposes. The study's results have not been reviewed by the FDA, EPA or any other governmental agency. Our products are not medical devices and are not intended to diagnose, treat, or cure any disease. We make no claims and no claims should be inferred as to the efficacy of our products to sanitize, disinfect or kill germs or other antimicrobials.

specifications

| | | |
|--------------------------------------|------------------------------|--|
| Air Scrubber Mini EM by Aerus | 9960022 | |
| electrical input | Input Voltage: 230 VAC | Current: 0.2A @ 120 VAC Power Factor: 0.99 Power: 20 Watts max |
| mechanical | Distribution via air handler | |
| operating temperature | 23F-131°F (-5° C to 55° C) | |
| dimensions | 29.75" L x 2.63" W x 1.25" H | 75.57 cm L x 6.67 cm W x 3.18 cm H |
| coverage | Up to 500 sq. ft. | |
| warranty | Limited 2 year warranty | |



Pol. Ind. Belartza.
Gurutzegi Kalea 17 Pab. D4 - D5
20018, San Sebastián
Tel. 943 377 740 | Fax: 943 376 923
Email: comercial@oxcontrol.es